

JWM-5000V5

A gun which is a must for every guard.



Multiple Device Support



Pogo Pin Connector



Water resistant



JWM-5000V5 (Security Guard Patrolling System)

GTS with a POGO Pin connector instead of normal USB port, which makes the device more guard proof and water proof. JWM5000V5 works with RFID tags with a simple non contact swipe, and can upload information via POGO pin connection.

Features:

- Military component
- Silicon tank, metal body with rubber shell outside, super durable IP67 standard
- POGO pin connecting cable, high download speed
- Non-contact reading of RFID tag
- Completely water proof and guard proof
- Sabotage absorbent, resistant to electrical shock
- Super storage capacity 16Mb Flash, 60000 records
- Power off protection
- REG colorful LED display
- Reading distance \leq 5 cm
- Real time internal clock



JWM-5000V5

RFID Guard Tour System

Hardware quick start guide

1. The patrolling guard takes the reader and read his own Guard ID to identify himself with the system
2. Then the guards go to the checkpoints, the Reader will automatically read each RFID tag and no need touch it. When reading successfully, a flash of the blue indicator light accompanied by a "vibration" means that a reading has been made. The JWM-5000V5 reader will store the signal card's ID number and time for every station reading.
3. After patrolling are done, use the USB cable to connect the computer and Reader directly and get a data analysis and management

Specification:

Dimensions:	144mm x 47mm x 30mm
Working Frequency:	125 Khz
Operating Temperature:	-45 ° to + 85 ° C
Memory:	16Mb Flash ROM
Storage Capacity:	60000 pieces of records
Battery:	3.7 V rechargeable battery, 800m Ah;
Signal Card Detection:	Auto induction card-reading
Card Reading Distance:	3cm -- -5cm
Communication:	POGO pin connecting cable 57600 BPS, 4000 records per minute
Weight:	227g



Specification: EMI Signal Card

Physical:	Water-resistant ant, ASB plastic case
Shape	Nail, button, circle, keyring and cylinder shape, etc.
Weight	About 2 g
Operating Temperature	-20° C to +50°C
Working Frequency	125KHz
Battery	None
Data Storage	Unique 64-bit serial number (read-only)

Charger



Input Voltage	AC 110V-220V, 50-60 HZ
Output Voltage	4.5V-14V, 300-500mA
Operating Standard	GB 4943-2001



Use POGO Pin connector as communication cable, which is according with DY/T1019, IEC61156, ANSI/EIA/TIA-568 standard



In4 Solution Pvt. Ltd.

No. 25, 1st Floor, Anna Main Road, M.G.R Nagar, (KK Nagar),
Near Muthoot Finance, Chennai - 600 078, Tamil Nadu.
Ph: 044- 42616446, 24710701. Email: biometric@in4solution.com